

Ice Merchandiser			Outside Dimensions			Glass Door	Ⓛ Approx. Wt.		Refrigeration	Amperage		
Models	No. of Doors	Capacity		Width (mm)	Ⓜ Ⓢ Depth (mm)	Height (mm)	Width x Height (mm)	Cold Wall (kg)	Auto Defrost (kg)	R404A Voltage 115/1/60	Cold Wall	Ⓛ Auto Defrost
		m ³ (approx.)	Bags* (3.5kg)									
L030UCGX L030UAGX	1	0.85	80 75	0914.4	762.0	1943.1	711.2 x 1193.8	145	156	.25kw	6.1	7.2
L040UCGX L040UAGX	1	1.10	170 160	1282.7	762.0	1943.1	711.2 x 1193.8	168	184	.25kw	6.1	7.2
L065UCGS L065UAGX	1	1.84	265 215	1625.6	901.7	1943.1	711.2 x 1193.8	206	220	.25kw	6.1	7.2
L063UCGX L063UAGX	2	1.78	265 245	1587.5	901.7	1943.1	660.4 x 1143	204	215	.37kw	6.5	7.4
L060UCGX L060UAGX	2	1.70	275 260	1854.2	762.0	1943.1	711.2 x 1193.8	231	245	.37kw	6.5	7.4
L075UCGX L075UAGX	2	2.12	290 275	1854.2	901.7	1943.1	711.2 x 1193.8	245	261	.37kw	6.5	8.3
L085UCGX L085UAGX	2	2.40	345 325	2133.6	901.7	1943.1	711.2 x 1193.8	268	281	.37kw	7.7	8.3
L100UCGX L100UAGX	2	2.83	400 380	2438.4	901.7	1943.1	711.2 x 1193.8	275	297	.37kw	7.7	9.6

MODEL IDENTIFICATION NUMBER DESCRIPTION

L | 030 | U | C | G | X

LEER	MODEL NUMBER	PROFILE	REFRIGERATION SYSTEM	DOOR TYPE	SPECIAL OPTIONS
		S = Slant U = Upright	C = Cold Wall A = Auto Defrost	G = Glass S = Solid	X = Standard V = Vinyl R = Refrigeration Upgrade

STANDARD FEATURES

- ▶ Total steel cabinet construction
- ▶ Baked-on acrylic polyurethane, high solids, lead-free, enamel finish exterior
- ▶ Full 63mm-thick, CFC-free, foamed-in-place polyurethane insulation in all walls and top with 76mm bottom insulation
- ▶ Low temperature sealed condensing units with service valves available on all models
- ▶ Interior air flow ducts on automatic defrost models
- ▶ Condensate evaporator on automatic defrost models
- ▶ Drop down evaporator system
- ▶ Triple-pane, tempered safety glass doors with self-closing hinges
- ▶ Illuminated interior
- ▶ Full top refrigeration cover
- ▶ Five year compressor warranty
- ▶ One year parts warranty

* Merchandiser storage capacity may vary due to type of ice, ice bag size differences and methods of loading.

- Ⓛ Shipping weight
- Ⓜ Add 88.9mm for door and handle
- Ⓢ Add 76mm for condensate evaporator
- Ⓛ Add 1.1 amps for condensate evaporator

OPTIONS

- ▶ Custom Painted Exterior
- ▶ 220/1/50 Voltage
- ▶ Heavy-duty Refrigeration (automatic defrost models only)
- ▶ Reverse Fan Self-cleaning Condensing Unit
- ▶ Finless Condensing Units
- ▶ Blue "ICE" Decals
- ▶ Gold or Black Frame Door
- ▶ LED Etched Glass Door.....
- ▶ LED Interior Lighting
- ▶ NeverMT™
- ▶ Diamond Plating
- ▶ Leveling Pads
- ▶ Electronic Control
- ▶ Shelving
- ▶ Heated Door
- ▶ Drop-in-refrigeration
- ▶ Partition



NOTE:

Glass door models are designed for use in stores where temperature and humidity are maintained at 24°C and 55% RH respectively.

Material and product improvement is a constant commitment at Leer, Inc. These specifications are subject to change without notice and without incurring responsibility for previously sold merchandisers and components.



An Employee Owned Company

Leer, Inc. • 206 Leer Street, New Lisbon, WI 53950 • 800.766.5337 • leerinc.com



ICE MERCHANDISERS



You make the ice.
We'll help you sell it.

LEADERS IN QUALITY

All Leer indoor merchandisers feature the finest cabinet construction assembled under the industry's toughest quality control standards. That means they'll be standing strong, ready to sell ice for many years to come.

LEADERS IN INNOVATION

Leer indoor merchandisers feature triple-pane, tempered safety glass doors; illuminated interior; full top refrigeration cover; quick recovery, low-temp, balanced refrigeration; total steel cabinet construction; and optional custom finishes. Innovations like these have helped us set industry standards for improving your return on investment.



MODEL L30



MODEL L60



MODEL L40



MODEL L75



MODEL L65



MODEL L85



MODEL L63



MODEL L100