

Ice Merchandiser				Outside Dimensions			Solid Door	Ⓢ Approx. Wt.		Refrigeration	Amperage	
Models	No. of Doors	Capacity		Width (mm)	Ⓢ Depth (mm)	Height (mm)	Width x Height (mm)	Cold Wall (kg)	Auto Defrost (kg)	R404A Voltage 115/1/60	Cold Wall	Auto Defrost
		m ³ (approx.)	Bags* (3.5kg)									
L040SCSX L040SASX	1	1.10	150 — 130	1282.7	901.7	1739.9	685.8 x 685.8	145	156	.25kw	6.1	7.2
L060SCSX L060SASX	2	1.70	235 — 210	1854.2	901.7	1739.9	685.8 x 685.8	181	197	.25kw	6.1	7.2
L075SCSX L075SASX	2	2.12	320 — 290	2438.4	901.7	1739.9	685.8 x 685.8	218	236	.37kw	7.5	9.2
L030UCSX L030UASX	1	0.85	80 — 75	914.4	762	1943.1	685.8 x 1168.4	127	138	.25kw	6.1	7.2
L040UCSX L040UASX	1	1.10	170 — 160	1282.7	762	1943.1	685.8 x 1168.4	147	159	.25kw	6.1	7.2
L065UCSX L065UASX	1	1.84	265 — 245	1625.6	901.7	1943.1	685.8 x 1168.4	184	195	.25kw	6.1	7.2
L060UCSX L060UASX	2	1.70	275 — 260	1854.2	762	1943.1	685.8 x 1168.4	193	206	.25kw	6.1	7.2
L075UCSX L075UASX	2	2.12	290 — 270	1854.2	901.7	1943.1	685.8 x 1168.4	204	222	.37kw	7.5	9.2
L085UCSX L085UASX	2	2.40	345 — 325	2133.6	901.7	1943.1	685.8 x 1168.4	229	240	.37kw	7.5	9.2
L100UCSX L100UASX	2	2.83	400 — 380	2438.4	901.7	1943.1	685.8 x 1168.4	240	254	.37kw	7.5	9.2
L462LCSX L462LASX	2	1.30	165 — 150	1854.2	901.7	1257.3	685.8 x 685.8	186	195	.25kw	6.1	7.4
L612LCSX L612LASX	2	1.72	230 — 210	2438.4	901.7	1257.3	685.8 x 685.8	210	225	.25kw	6.1	7.4

MODEL IDENTIFICATION NUMBER DESCRIPTION

L | 040 | S | C | S | X

LEER	MODEL NUMBER	PROFILE	REFRIGERATION SYSTEM	DOOR TYPE	SPECIAL OPTIONS
		L = Low S = Slant U = Upright	C = Cold Wall A = Auto Defrost	G = Glass S = Solid	X = Standard V = Vinyl R = Refrigeration Upgrade

STANDARD FEATURES

- ▶ Total steel cabinet construction
- ▶ Baked-on acrylic polyurethane, high solids, lead-free, enamel finish exterior
- ▶ Full 63.5mm-thick, CFC-free, foamed-in-place polyurethane insulation in all walls and top with 76mm bottom insulation
- ▶ Low temperature sealed condensing units with service valves available on all models
- ▶ Reinforced, embossed Durapon Coated steel doors with welded PVC frame and roll-in gaskets
- ▶ Drop down evaporator systems
- ▶ Interior air flow ducts on automatic defrost models
- ▶ Five year compressor warranty
- ▶ One year parts warranty

* Merchandiser storage capacity may vary due to type of ice, ice bag size differences and methods of loading.

- Ⓢ Shipping weight
- Ⓢ Add 76mm for door and handle on upright models
- Ⓢ Add 76mm for raceway/stand off

OPTIONS

- ▶ Custom Painted Exterior
- ▶ 220/1/50 Voltage
- ▶ Heavy-duty Refrigeration (automatic defrost models only)
- ▶ Reverse Fan Self-cleaning Condensing Unit
- ▶ Blue "ICE" Decals
- ▶ NeverMT™
- ▶ Diamond Plating
- ▶ Leveling Pads
- ▶ Electronic Control
- ▶ Shelving
- ▶ Heated Door
- ▶ Drop-in-refrigeration
- ▶ Partition

Material and product improvement is a constant commitment at Leer, Inc. These specifications are subject to change without notice and without incurring responsibility for previously sold merchandisers and components.



An Employee Owned Company

Leer, Inc. • 206 Leer Street, New Lisbon, WI 53950 • 800.766.5337 • leerinc.com



ICE MERCHANTS



You make the ice.
We'll help you sell it.

LEADERS IN QUALITY

All Leer outdoor merchandisers feature the finest cabinet construction assembled under the industry's toughest quality control standards. That means they'll be standing strong, ready to sell ice for many years to come.

LEADERS IN INNOVATION

Leer outdoor merchandisers feature reinforced, embossed Durapon Coated steel doors with welded PVC frame; total steel cabinet construction; optional custom finishes; and quick recovery, low-temp, balanced refrigeration. Innovations like these have helped us set industry standards for improving your return on investment.



MODEL L40
SLANT



MODEL L60
SLANT



MODEL L75
SLANT



MODEL L30



MODEL L40



MODEL L65



MODEL L60



MODEL L75



MODEL L85

MODEL L100



MODEL L462



MODEL L612